


Integrated Control Unit

Appearance	SN.	Item	Detail		
	1	Model	JRI-CU-01		
	2	UHF Frequency	865MHz ~ 868MHz; 902MHz ~ 928MHz		
	3	Air Protocol	ISO 18000-6C EPC Class 1 Gen 2		
	4	Output Power	0~33dBm		
	5	Output Power Accuracy	±1dBm		
	6	System Configuration	CPU	Intel Core i5-10500H	
			RAM	16G	
			Hard Disk	512G SSD	
	7	Storage Capacity of RFID Tags	≥5000PCS (Model: J31)		
	8	Access Control Integration	Account password, finger vein identification, IC/ID card identification		
	9	Communication	Communication Wi-Fi, Bluetooth, Cellular Data Network, Wired Network (RJ45)		
	10	Power Supply	AC 100-240V 50/60Hz		
	11	Power	≤350W		
	12	Operating Voltage	DC12-24V		
	13	Operating Environment	-10°C ~ +40°C; ≤90% RH (No-condensing)		
	14	External Dimension (L*W*H)	550mm*510mm*1400mm		
	15	Net Weight	55 kg		
16	Packing Dimension (L*W*H)	650mm*610mm*1500mm			
17	Gross Weight	85 kg			